

ExamsLabs

ExamsLabs

HOME

ALL VENDORS

GUARANTEE

FAQ

TESTIMONIALS

CART (0)

Pass Your Next Certification Exam Fast!

Everything you need to prepare, learn & pass your certification exam easily.

365 days free updates. First attempt guaranteed success.



Select a vendor...

Select an test...

Your email address

Free Download Demo

Try **Online Engine** before you buy

Online Test Engine: Online Tool, Convenient, easy to study. Instant Online Access. Supports All Web Browsers.

PDF format: Easy to read and print learning materials, our products are available in PDF file format.

Desktop Test Engine: Installable Software Application. Simulates Real Exam Environment. Practice Offline Anytime.

What Client's Say

"I passed today with score 80%. I confirm that it's valid in UK. Focus on "Correct answer" and forget the "Answer X from real test". I had free new questions.



Sebastian
★★★★★

"Questions from this HPE0-S51 dump are 100% valid... not all answers. I passed this exam a few days ago (in France) and got these results.



Wayne
★★★★★

<http://www.examslabs.com/>

Latest Study Materials, Valid Dumps - ExamsLabs

Exam : **NS0-173**

Title : Cisco and NetApp FlexPod
Design Specialist

Vendor : Network Appliance

Version : DEMO

NO.1 A customer with a FlexPod Express solution wants to enable remote access to the NetApp storage component.

In this scenario, which two access methods are recommended? (Choose two.)

- A. Telnet
- B. SAML
- C. SSH
- D. RDP

Answer: A,C

NO.2 You are configuring Cisco UCS servers for FC SAN boot and want to perform zoning on your Cisco Nexus 5000 series switches.

In this scenario, which statement is correct?

- A. FC zoning on the Nexus series switches is not supported; zoning can be done only on the Cisco Fabric Interconnects.
- B. The corresponding FC ports on your NetApp storage array must be configured in LACP mode.
- C. SAN links are required between the Cisco Fabric Interconnects and the Nexus 5000 switches.
- D. An iSCSI license on the NetApp storage controller is required.

Answer: A

NO.3 Which two NetApp storage controllers would be used in a valid FlexPod Datacenter configuration? (Choose two.)

- A. NetApp EF570
- B. NetApp AFF A700
- C. NetApp E2800
- D. NetApp FAS2700

Answer: B,D

NO.4 A client has a FlexPod Datacenter solution with four active fabric links in port channel mode established between the Cisco Fabric Interconnects and the IOMs on a Cisco 5108 blade chassis. The blade chassis is fully populated with Cisco UCS B200M5 blades. A worker in the data center inadvertently unplugs the fourth uplink cable from IOM-A while working in the rack.

In this scenario, what happens to the network traffic?

- A. There is a loss of connectivity for servers 4 and 8.
- B. Traffic is load-balanced within IOM-A.
- C. Connectivity for servers 3, 4, 7, and 8 all fail over to IOM-B.
- D. Traffic is load-balanced within IOM-B.

Answer: C

NO.5 Your customer has a FlexPod implementation and wants to use life-cycle management to validate, monitor, and optimize the FlexPod infrastructure.

In this situation, which management tool should your customer use?

- A. NetApp Converged System Advisor
- B. Cisco UCS Manager

C. NetApp OnCommand Unified Manager

D. Cisco UCS Director

Answer: D